

Colour-matched end-cut preservative for pressure treated wood projects



***If you cut it,
coat it!***

Penetrating wood preservative and moisture repellent that protects cuts and holes in pressure treated wood from fungal decay.

- ▶ For use **above-ground [cut and holes ONLY in deck boards, post tops, fence boards, etc.]** where appearance counts
- ▶ Soft green colour closely matches pressure treated wood
- ▶ Can be applied directly from the can, for less clean-up
- ▶ 946 ml covers 40-140 sq. ft. (4-13 m²), depending on porosity of the wood
- ▶ Proof of purchase of end-cut preservative at time of construction is required for pressure treated wood lifetime limited residential warranty

www.EndCoat.ca

The Preservative

EndCoat™ Wood Preservative is a 2% solution of Zinc Naphthenate in Mineral Spirits.

(This solution is not intended to replace pressure treatment.)

Uses

Use EndCoat™ Wood Preservative for all cuts and holes in pressure treated wood that expose untreated wood **above ground – cut and holes ONLY in deck boards, post tops, fence boards, etc.**, where appearance counts.

Do not apply to wood or fabric or any surface where prolonged skin contact may occur, or any surface which may come into contact with food, feed or drinking water.

DO NOT use to recoat pressure treated wood surfaces.

For exterior use only.

Application

- ▶ The wood surface to be coated should be clean and dry prior to application.
- ▶ Use a small disposable bristle or sponge brush to apply the preservative directly from the can as supplied; do not dilute.
- ▶ Mix before use and stir frequently.
- ▶ Liberally brush coat the exposed untreated surface with preservative, allow to dry and re-coat.
- ▶ Allow to dry thoroughly before permitting contact.

Clean-Up

- ▶ Clean brushes with mineral spirits, then with detergent and water.

Detailed instructions are printed on the product label. Follow the manufacturer's recommendations on the product label.

