SAFETY DATA SHEET



1. Identification

Product identifier NW-CA-B Treated Wood

Other means of identification 313-TIM-E

Recommended use Preservative Treated Wood for various interior and exterior applications.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Customers of Timber Specialties Co.

Company name

Address

Telephone number

Emergency phone number

E-mail

2. Hazard(s) identification

Physical hazardsCombustible dustsCategory 1Health hazardsCarcinogenicityCategory 1A

Label elements Hazard symbols

Signal word Danger

Hazard statement May cause cancer by inhalation. May form combustible dust concentrations in air.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Prevent dust accumulation to minimize explosion hazard. Ground/bond container and receiving equipment. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of

water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated

clothing and wash before reuse. In case of fire: Use CO2, foam or water spray for

extinction.

Storage Store in a well-ventilated place.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise classified

(HNOC)

May cause respiratory irritation. Depending on wood species may cause respiratory

sensitization and/or irritation.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Wood/Wood dust	N/A	> 90	
Copper ethanolamine complex (expressed as elemental copper)	14215-52-2	< 1	
Tebuconazole	107534-96-3	< 1	

Composition comments

Depending on the additives applied to the treating solution, this wood may also contain <1 % of mold inhibitors, <1% of a wax emulsion, and <1% of a colorant. Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Skin contact

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. Some species may

cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals.

Wash off with soap and water. Get medical attention if irritation develops and persists. Prolonged contact with treated wood and/or treated wood dust, especially when freshly treated at the plant, may cause irritation to the skin. Abrasive handling or rubbing of the treated wood may increase skin irritation. Some wood species, regardless of treatment, may cause dermatitis or allergic skin reactions in sensitized individuals. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

Eye contactDo not rub eye. Immediately flush eye(s) with plenty of water. Remove any contact lenses

and open eyelids wide apart. If eye irritation persists, get medical attention.

Ingestion Rinse mouth thoroughly if dust is ingested. Get medical attention if any discomfort continues.

Most important symptoms/effects, acute and delayed Wood dust: May cause nasal dryness, irritation and mucostasis. Coughing, wheezing, sneezing, sinusitis and prolonged colds have also been reported. Depending on wood

sneezing, sinusitis and prolonged colds have also been reported. Depending on wood species may cause respiratory sensitization and/or irritation. Mechanical irritation of skin, over and requirement system.

eyes and respiratory system.

Indication of immediate medical attention and special treatment needed General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Depending on moisture content, and more importantly, particle diameter and airborne concentration, wood dust in a contained area may explode in the presence of an ignition source. Wood dust may similarly deflagrate (combustion without detonation like an explosion) if ignited in an open or loosely contained area. An airborne concentration of 40

grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards- 654 and 664 for guidance.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire-fighting equipment/instructions

Use water spray to cool fire exposed surfaces and to protect personnel.

6. Accidental release measures

Personal precautions, protective Eliminate all ignition sources (no sm equipment and emergency procedures generation and spreading of dust. A

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid generation and spreading of dust. Avoid spread of dust. Avoid inhalation of dust. Provide adequate ventilation. Wear appropriate personal protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Sweep or vacuum up spillage and collect in suitable container for disposal. If not possible, gently moisten dust before it is collected with shovel, broom or the like. Containers must be labeled. For waste disposal, see Section 13.

Environmental precautions For good industrial practice avoid release to the environment.

7. Handling and storage

Precautions for safe handling Avoid working with freshly treated wet wood. If not possible, wear long sleeve shirt, long

pants and gloves when working with freshly treated wet wood. Clothing should be removed and replaced if it becomes wet due to contact with freshly treated wood. Avoid prolonged or repeated breathing of dust. Avoid prolonged or repeated contact with skin. Do not smoke. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear appropriate personal protective equipment (See Section 8). Do not burn

preserved wood. Do not use preserved wood as mulch.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a dry, cool and well-ventilated place. Store away from incompatible materials (See Section 10).

NW-CA-B Treated Wood SDS US

2/7

8. Exposure controls/personal protection

Occupational exposure limits

110	ACCIL	Throc	hald	Limit	Values
US.	ACGIH	Inres	noia	LIMIT	values

Components	Туре	Value	Form
Wood/Wood dust (CAS N/A)	TWA	1 mg/m ³	Inhalable Fraction
Monoethanolamine (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	
Copper (as metal)	TWA	1 mg/m ³	Dust and mist.
		0.2 mg/m ³	Fume.
Canada. Alberta OELs (Occupational Hea	Ith & Safety Code, Schedule 1,	Table 2)	
Components	Type	, Value	Form
Wood/Wood dust (CAS N/A)	TWA	0.5 mg/m ³	Total Dust
Monoethanolamine (CAS 141-43-5)	STEL	15mg/m ³ , 6 pp	om
	TWA	7.5 mg/m³, 3 բ	ppm
Canada. British Columbia OELs. (Occupa	tional Exposure Limits for Che	mical Substances, Occupation	al Health and
Salety Regulation 230/31, as affended)			
Components	Туре	Value	Form
,	Type TWA	Value 1 mg/m³	Form Dust
Components			
Wood/Wood dust (CAS N/A)	TWA	1 mg/m ³	
Components Wood/Wood dust (CAS N/A)	TWA STEL TWA	1 mg/m³ 6 ppm 3 ppm	

Canada.	Ontario (DELs. (Control of	Exposure t	o Biological	or Chemical Agents)
		,				

Wood/Wood dust (CAS N/A)	STEL	10 mg/m ³	Dust
	TWA	1 mg/m ³	Dust
Monoethanolamine (CAS 141-43-5)	STEL TWA	6 ppm 3 ppm	

Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

TWA

TWA

Wood/Wood dust (CAS N/A)	TWA	2.5 mg/m ³ Dust
Monoethanolamine (CAS 141-43-5)	STEL TWA	15 mg/m³, 6 ppm 7.5 mg/m³, 3 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Provide sufficient general/local exhaust ventilation to maintain inhalation exposures below current exposure limits and areas below explosive dust concentrations. Shower, hand and

eye washing facilities near the workplace are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields or safety goggles when sawing or cutting.

Skin protection

Copper (as metal)

Hand protection When handling wood, wear leather or fabric gloves. Chemical resistant gloves may be

necessary for handling freshly treated wood.

Other Wear long sleeve shirt, pants, and closed-toed shoes when handling wood.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Wear dust mask

when sawing or sanding wood. If exposure limits are exceeded or if irritation is experienced, a NIOSH-approved positive pressure self-contained breathing apparatus

3 ppm 1 mg/m³

0.2 mg/m³

Dust and mist.

Fume.

should be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

If wood dust contacts the skin, workers should wash the affected areas with soap and water. Clothing contaminated with wood dust should be removed, and provisions should be made for the safe removal of the chemical from the clothing. Persons laundering the clothes should be informed of the hazardous properties of wood dust. A worker who handles wood dust should thoroughly wash hands, forearms, and face with soap and water before eating, using tobacco products, using toilet facilities, applying cosmetics, or taking medication. Workers should not eat, drink, use tobacco products, apply cosmetics, or take medication in areas where wood dust is handled, or processed. Observe any medical surveillance requirements.

9. Physical and Chemical Properties

Appearance

Physical state Solid. Chips. Dust. Form Color Not available. Odor Wood odor. **Odor threshold** Not available. pН Not applicable. Melting point/freezing point Not applicable. Initial boiling point and boiling range Not applicable. **Flash Point** Not available. **Evaporation rate** Not applicable. Flammability (solid, gas) Combustible dust.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)
Flammability limit - upper (%)
Explosive limit - lower (%)
Explosive limit - upper (%)
Not available.
Explosive limit - upper (%)
Not available.
Vapor pressure
Vapor density
Relative density
Not available.
Not available.

Solubility(ies)

Solubility (water)

Partition coefficient (n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available.

Not applicable.

Not available.

Not applicable.

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous reactionsHazardous reactions do not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Minimize dust generation and

accumulation. Avoid contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Reducing agents.

Hazardous decomposition products Combustion products may yield irritating and toxic fumes and gases including organic

chloride, aldehydes, amines, hydrogen chloride, ammonia, copper compounds, oxygen,

boric oxide, oxides of carbon and nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Wood dust, treated or untreated, is irritating to the nose, throat and lungs. Prolonged or repeated inhalation of wood dusts may cause respiratory irritation, recurrent bronchitis and prolonged colds. Some species may cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals. Prolonged exposure to wood dusts by inhalation has been reported to be associated with nasal and paranasal cancer.

Skin contactDust may irritate skin. Handling may cause splinters. Prolonged contact with treated wood

and/or treated wood dust, especially when freshly treated at the plant, may cause irritation to the skin. Abrasive handling or rubbing of the treated wood may increase skin irritation. Some wood species, regardless of treatment, may cause dermatitis or allergic skin reactions in

sensitized individuals.

Eye contact Dust may irritate the eyes.

Ingestion Not likely, due to the form of the product. However, ingestion of dusts generated during

lung irritation and other respiratory effects.

working operations may cause nausea and vomiting. Certain species of wood and their

dusts may contain natural toxins, which can have adverse effects in humans.

Symptoms related to the physical,

chemical and toxicological

characteristics

Wood dust: May cause nasal dryness, irritation and mucostasis. Coughing, wheezing, sneezing, sinusitis and prolonged colds have also been reported. Depending on wood species may cause respiratory sensitization and/or irritation. Symptoms can include irritation, redness, scratching of the cornea, and tearing. May cause eczema-like skin disorders (dermatitis). Airborne treated or untreated wood dust may cause nose, throat, or

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

 Tebuconazole (CAS 107534-96-3)
 Rat
 > 5000 mg/kg

 Oral LD50
 Rat
 1517 mg/kg

 Inhalation LC50
 Rat
 > 2.07 mg/l

Skin corrosion/irritationDust may irritate skin.Serious eye damage/eye irritationDust may irritate the eyes.

Respiratory or skin sensitization

ACGIH Sensitization

Wood/Wood dust (CAS N/A) Dermal sensitization. Respiratory sensitization.

Canada - Alberta OELs: Irritant

Monoethanolamine (CAS 141-43-5 Irritant.

Canada - Manitoba OELs Hazard: Dermal sensitization

Wood/Wood dust (CAS N/A) Dermal sensitization

Canada - Manitoba OELs Hazard: Respiratory sensitization

Wood/Wood dust (CAS N/A) Respiratory sensitization

Canada - Saskatchewan OELs Hazard Data: Sensitiser

Wood/Wood dust (CAS N/A) Sensitizer

Respiratory sensitization Exposure to wood dusts can result in hypersensitivity.

Skin sensitization Exposure to wood dust can result in the development of contact dermatitis. The primary

irritant dermatitis resulting from skin contact with wood dusts consist of erythema, blistering,

and sometimes erosion and secondary infections occur.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer by inhalation. This classification is based on an increased incidence of

nasal and paranasal cancers in people exposed to wood dusts.

ACGIH Carcinogens

Wood/Wood dust (CAS N/A) A1 Confirmed human carcinogen. A2 Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Wood/Wood dust (CAS N/A) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Wood/Wood dust (CAS N/A) Known To Be Human Carcinogen.

Canada - Manitoba OELs: carcinogenicity

Wood/Wood dust (CAS N/A) Confirmed human carcinogen. Suspected human carcinogen.

US. National Toxicology Program (NTP) Report on Carcinogens

Wood/Wood dust (CAS N/A) Known To Be Human Carcinogen

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not likely, due to the form of the product.

Chronic effects

Chronic exposure to wood dusts can result in pneumonitis, and coughing, wheezing, fever and the other signs and symptoms associated with chronic bronchitis. . Individuals with pre-existing disease in or a history of ailments involving the skin, kidney, liver, respiratory tract, eyes, or nervous system are at a greater than normal risk of developing adverse effects from

Test Results

woodworking operations with this product.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. This product is not expected to leach

harmful amounts of preservative into the environment.

Species Components Copper ethanolamine complex (CAS 14215-52-2) Crustacea EC50 0.56-0.94 mg/L, 48 hours Fish LC50 1.3-1.7 mg/L, 48 hours Copper (as metal) Algae EC50 0.011-0.017 mg/L, 72 hours 0.03-0.058 mg/L, 96 hours Algae EC50 Crustacea EC50 0.0006-0.0017 mg/L, 48 hours Fish I C50 0.003 ma/L. 96 hours Fish NOEC 0.00009 mg/L, 48 hours Tebuconazole (CAS 107534-96-3) Algae EC50 2.09-3.01 mg/L, 72 hours Algae EC50 1.45 mg/L, 96 hours Crustacea EC50 2.1-3.94 mg/L, 48 hours

Crustacea NOEC Fish LC50

No data is available on the degradability of this product.

Bioaccumulative potential

Persistence and degradability

Partition coefficient n-octanol / water (log Kow)

Tebuconazole (CAS 107534-96-3) 5.4673

Mobility in soil The product is insoluble in water.

Mobility in general The product is not volatile but may be spread by dust-raising handling.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

0.000987 mg/L, 672 hours

6.4 mg/L, 96 hours

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Do not discharge into

drains, water courses or onto the ground.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose in accordance with all applicable regulations. Do not discharge into drains, water courses

or onto the ground.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG Not regulated as dangerous goods. **IATA** Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International Regulations

Stockholm ConventionNot applicable.Rotterdam ConventionNot applicable.Kyoto protocolNot applicable.Montreal ProtocolNot applicable.Basel ConventionNot applicable.

International Inventories Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Inventory name

Issue date 11/16/2023

Revision date - 01

Special instructions If you expect to generate wood dust, read Sections 4, 7, 8, and 11.

Retention levels PERCENTAGE OF ACTIVE INGREDIENTS PER RETENTION LEVEL

End Use	Target Retention (kg/m3)
Above Ground	1.7
Ground Contact	3.3
Ground Contact (Severe Decay Hazard)	5.0

Disclaimer

Supplier cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

NW-CA-B Treated Wood SDS US

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).